



SCANNELL HAY EQUIPMENT

2 Bale Trailing Feeder TR

UNBEATABLE QUALITY
& PERFORMANCE

'Buy the best,
forget the rest'



- Market leading design
- Proven performance

Built to withstand New Zealand's extreme climate and terrain
with heavy duty, robust, design and construction

Manufactured By


B.J. Scarlett Ltd
MANUFACTURERS AND ENGINEERS

Phone (03) 688 2900 Email sales@scarlett.co.nz



2 Bale Trailing Feeder

Capacity

2 Round Bales.

Features

- Patented Twin Rotor Feed system. The left side is lower and travelling 20% faster than the right side, giving two different feed patterns. Finishes cores quickly without wedging. Delivers excellent performance.
- Heavy-duty 4.4 tonne capacity hub assemblies.
- Hub shields protect seals from hay and twine.
- Low centre of gravity and excellent ground clearance.
- Left hand side lowers down level to allow bales to be carried and unloaded. This is also lowered for feeding square bales.
- Full width anti-wrap / deflector bar, feeds product clear of the wheels.
- Two stage loading forks with adjustable free running slider platform.
- 2" Heavy duty zinc plated floor chain with high tensile battens.
- Full sheet metal adjustable floor to protect shafts from wrapping with product.
- Robust 125x75x5mm RHS chassis rails.
- Heavy duty towing eye. Ø40mm hole.
- Spring tensioned drive chains.
- Wide all weather tread 10.0/75-15.3 flotation tyres.
- Steel drive chain covers.
- Hydraulic hose end holder.
- Fully sandblasted and painted with 2 pack Urethane.
- Removable Jack and separate carry brackets.
- Weight approx. 880 kg.

Options

- BKT Tractor grip tyres.

Specifications may change without notice