



SCANNELL HAY EQUIPMENT

5 Bale Trailing Feeder and Loading Fork

UNBEATABLE QUALITY
& PERFORMANCE

'No need to get
caught SHORT!'



- Save your valuable time and tractor hours by carrying more bales at one time
- Quick easy loading
- Reliable, efficient feeding

Built to withstand New Zealand's extreme climate and terrain
with heavy duty, robust, design and construction

Manufactured By



B.J. Scarlett Ltd

MANUFACTURERS AND ENGINEERS

Phone (03) 688 2900 Email sales@scarlett.co.nz



Features 5 BT Trailing Feeder

For Feeding out or Transporting Round Bales from the field.

Capacity

5 Round Bales.

Features

- Patented Twin Rotor Feed. The left side is lower and travelling 20% faster than the right side, giving two different feed patterns. Finishes cores quickly without wedging. Delivers excellent performance.
- Heavy-duty hub assemblies with hub shields to protect seals from hay and twine.
- Folded plate tandem axles with high tensile bronze pivot bushes.
- Axle centre pivot is offset so that the front tyres carry less weight for better turning and soft ground performance.
- Full sheet metal adjustable floor to protect shafts from wrapping with product.
- Full sheet metal adjustable feed floor also protects shafts.
- 2" Heavy duty zinc plated floor chain with 40x40 'Duragalv' battens.
- Robust 150x75x5mm RHS chassis rails with 100x75x5mm RHS doubled section.
- Fully sandblasted and painted with 2 pack Urethane.
- Drop side for unloading bales.
- 11.5/80x15.3 tyres.
- Spring tensioned drive chains.
- Steel drive chain covers.
- Heavy duty jack.
- Side self loading forks.
- Weight = Approx. 2220 kg.

Specifications may change without notice